




Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05)






PART NUMBER CODING

PHDS17-12 XX XX X XXX X 1

No. of Pins 01-50	Contact Plating G0:Gold Flash G1:3U"Gold G2:5U"Gold G3:10U"Gold G4:15U"Gold G5:20U"Gold G6:30U"Gold S0:Gold Flash/Tin S1:3U"Gold/Tin S2:5U"Gold/Tin S3:10U"Gold/Tin S4:15U"Gold/Tin S5:20U"Gold/Tin S6:30U"Gold/Tin SN:Tin	Insulator Material/Colour A:PBT/Black B:PA9T/Black C:PA6T/Black	Pin length L=A+B+1.75	Packing A=Tray B=PE bag T=Tube
----------------------	---	---	--------------------------	---

Dimensions Antitheses List		
Part No.	A	B
PHDS17-12XXXXXX065X1	1.80	3.00



Tel: +86 769 82581808 FAX: +86 769 81766192
E-Mail: sales@winpin.net Http: www.winpin.net

PART NO: PHDS17-12XXXXXXXXXX1

TITLE: PH 1.27x2.54mm Dual ROW 180°SMT H=1.7mm

NOTES:
Current Rating:1.0AMP
Withstand Voltage:500V AC/DC
Contact Resistance:20mΩ Max
Insulation Resistance:1000MΩ Min
Operation Temperature:-40°C to +105°C

Contact Material:Brass
Contact Plating:Au or Sn over Ni
Insulator Material:PBT/PA9T/PA6T+30%GF
(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X:±0.40 ± 3°
X.XX:±0.25
X.XXX:±0.15

SCALE	1:1
UNIT	MM
PROJ.	
SHEET	

A0	2015/06/25	NEW	Huan.Tan		Huan.Tan
REV	DATE	MODIFICATION DESCRIPTIO	DRAW	CHANGE	APPROVE