




Recommended P.C.B Layout(Top Side)
(PCB BOARD TOL ERANCE ± 0.05)



PART NUMBER CODING

MFFS30-2 XX XX X 074 X 3



No. of Pins
02-40pin

Contact Plating

G0:Gold Flash
G1:3U"Gold
G2:5U"Gold
G3:10U"Gold
G4:15U"Gold
G5:20U"Gold
G6:30U"Gold
S0:Gold Flash/Tin
S1:3U"Gold/Tin
S2:5U"Gold/Tin
S3:10U"Gold/Tin
S4:15U"Gold/Tin
S5:20U"Gold/Tin
S6:30U"Gold/Tin
SN:Tin

Insulator
Material/Colour
A:PPS/Black

Packing
A:Tray
B:PE Bag
T:Tube



WINPIN

Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: MFFS30-2XXXXX074X3

TITLE: 2.54mm Machined Female Header 180° H=3.0 L=7.4mm

NOTES:
Current Rating: 3.0AMP
Contact Resistance: 10MΩ Max
Withstand Voltage: 1000V RMS Min
Mechanical Life: Min 500 cycles
Connecting Pin: Ø0.50mm
Operation Temperature: -40°C to +105°C

Material
Sleeve: Brass
Contact Plating: Au or Sn over Ni
Insulator Material: PPS(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X: ± 0.30
X.XX: ± 0.25
X.XXX: ± 0.15

SCALE 1:1
UNIT MM
PROJ.
SHEET

A0	2015/06/25	NEW	Huan.Tan		Huan.Tan	
REV	DATE	MODIFICATION DESCRIPTION	DRAW	CHANGE	APPROVE	