




Recommended P.C.B Layout(Top Side)
(PCB BOARD TOL ERANCE±0.05)




PART NUMBER CODING
MFFS30-2 XX XX X 074 X 1

No.of Pins
02-40pin

Contact Plating
G0:Gold Flash
G1:3U*Gold
G2:5U*Gold
G3:10U*Gold
G4:15U*Gold
G5:20U*Gold
G6:30U*Gold
S0:Gold Flash/Tin
S1:3U*Gold/Tin
S2:5U*Gold/Tin
S3:10U*Gold/Tin
S4:15U*Gold/Tin
S5:20U*Gold/Tin
S6:30U*Gold/Tin
SN:Tin

Insulator
Material/Colour
A:PPS/Black

Packing
A:Tray
B:PE Bag
T:Tube



Tel:+86 769 82581808
E-Mail:sales@winpin.net

FAX:+86 769 81766192
Http:www.winpin.net

PART NO: MFFS30-2XXXXX074X1

TITLE: 2.54mm Machined Female Header 180° H=3.0 L=7.4mm

NOTES:
Current Rating:3.0AMP
Contact Resistance:10MΩ Max
Withstand Voltage:1000V RMS Min
Mechanical Life:Min 500 cycles
Connecting Pin:Ø0.50mm
Operation Temperature:-40°C to +105°C

Material
Sleeve:Brass
Contact Plating:Au or Sn over Ni
Insulator Material:PPS(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X:±0.30 ± 3°
X.XX:±0.25
X.XXX:±0.15

SCALE 1:1
UNIT MM
PROJ.
SHEET

A0	2015/06/25	NEW	Huan.Tan		Huan.Tan	
REV	DATE	MODIFICATION DESCRIPTION	DRAW	CHANGE	APPROVE	