

DETAIL A
SCALE: 4/ 1

PART NUMBER CODING

MFEM28-2 XX XX X 065 X X


No. of Pins
02-40pin

Contact Plating
G0:Gold Flash
G1:3U"Gold
G2:5U"Gold
G3:10U"Gold
G4:15U"Gold
G5:20U"Gold
G6:30U"Gold
S0:Gold Flash/Tin
S1:3U"Gold/Tin
S2:5U"Gold/Tin
S3:10U"Gold/Tin
S4:15U"Gold/Tin
S5:20U"Gold/Tin
S6:30U"Gold/Tin
SN:Tin


Insulator
Material/Colour
A:PPS/Black

Packing
A:Tray
T:Tube
P:Tube+CAP
R:Tapd&Reel+CAP
M:Tapd&Reel+Mylar


Series
1:TYPE1(WITH POST)
2:TYPE2(W/O POST)



TYPE 2(W/O POST)



TYPE 1(WITH POST)



WINPIN

Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: MFEM28-2XXXXX065XX

TITLE: 2.00mm Machined Female Header SMT H=2.80 L=6.50

NOTES:
Current Rating: 2.0AMP
Contact Resistance: 10mΩ Max
Withstand Voltage: 1000V RMS Min
Mechanical Life: Min 500 cycles
Connecting Pin: Ø0.50mm
Operation Temperature: -40°C to +105°C

Material
Sleeve: Brass
Contact Plating: Au or Sn over Ni
Insulator Material: PPS(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X: ±0.40 ± 3°
X.XX: ±0.25
X.XXX: ±0.15

SCALE 1:1
UNIT MM
PROJ. 
SHEET

A0	2015/06/25	NEW	Huan.Tan		Huan.Tan
REV	DATE	MODIFICATION DESCRIPTIO	DRAW	CHANGE	APPROVE