


Recommended P.C.B Layout(TOP Side)
(PCB BOARD TOLERANCE ± 0.05)



PART NUMBER CODING

FHFM71- 2 XX XX X U X X




No.of Pins
Row:02-40Pin

Contact Plating
G0:Gold Flash
G1:3U"Gold
G2:5U"Gold
G3:10U"Gold
G4:15U"Gold
G5:20U"Gold
G6:30U"Gold
S0:Gold Flash/Tin
S1:3U"Gold/Tin
S2:5U"Gold/Tin
S3:10U"Gold/Tin
S4:15U"Gold/Tin
S5:20U"Gold/Tin
S6:30U"Gold/Tin
SN:Tin

Insulator
Material/Colour
B:PA9T/Black
C:PA6T/Black

Packing
T=Tube
P=Tube+Cap
R=Tape&Reel+Cap

Type
1:Type1
2:Type2



WINPIN

Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: FHFM71-2XXXXXX

TITLE: FH2.54mm Dual Female H=7.1mm SMT PC7.2mm

NOTES:
Current Rating:3.0AMP
Contact Resistance:20m Ω Max
Insulation Resistance:1000M Ω Min
Withstand Voltage:1000V AC
Operation Temperature: -40°C to +105°C

MATERIAL:
Contact Material:Brass
Contact Plating: Au or Sn over Ni
Insulator Material:PA9T/PA6T+30%GF
(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X: ± 0.40 $\pm 3^\circ$
X.XX: ± 0.25
X.XXX: ± 0.15

SCALE 1:1
UNIT MM
PROJ. 
SHEET

\$						
	A0	2015/06/25	NEW	GF.He	_____ Andy	
	REV	DATE	MODIFICATION DESCRIPTIO	DRAW	CHANGE	APPROVE