




Recommended P.C.B Layout(TOP Side)
(PCB BOARD TOLERANCE ± 0.05)



PART NUMBER CODING




FHFS71- 2 XX XX X U X 1

No. of Pins
Row: 02-40 Pin

Contact Plating
G0: Gold Flash
G1: 3U*Gold
G2: 5U*Gold
G3: 10U*Gold
G4: 15U*Gold
G5: 20U*Gold
G6: 30U*Gold
S0: Gold Flash/Tin
S1: 3U*Gold/Tin
S2: 5U*Gold/Tin
S3: 10U*Gold/Tin
S4: 15U*Gold/Tin
S5: 20U*Gold/Tin
S6: 30U*Gold/Tin
SN: Tin

Insulator
Material/Colour
A: PBT/Black
B: PA9T/Black
C: PA6T/Black

Packing
A=Tray
T=Tube



Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: FHFS71-2XXXXXUX1

TITLE: FH2.54mm Dual Female H=7.1mm 180° PC=3.2mm

NOTES:
Current Rating: 3.0AMP
Contact Resistance: 20m Ω Max
Insulation Resistance: 1000M Ω Min
Withstand Voltage: 500V AC/Minute
Operation Temperature: -40°C to +105°C

MATERIAL:
Contact Material: Brass
Contact Plating: Au or Sn over Ni
Insulator Material: PBT/PA9T/PA6T+30%GF
(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X: ± 0.40 $\pm 3^\circ$
X.XX: ± 0.25
X.XXX: ± 0.15

SCALE 1:1
UNIT MM
PROJ.
SHEET

S					
	A0	2015/06/25	NEW	GF.He	_____ Andy
	REV	DATE	MODIFICATION DESCRIPTIO	DRAW	CHANGE APPROVE