



PART NUMBER CODING



FHFM34- 1 XX XX X U X 1

No. of Pins
Row: 02-40 Pin

Contact Plating
G0: Gold Flash
G1: 3U*Gold
G2: 5U*Gold
G3: 10U*Gold
G4: 15U*Gold
G5: 20U*Gold
G6: 30U*Gold
S0: Gold Flash/Tin
S1: 3U*Gold/Tin
S2: 5U*Gold/Tin
S3: 10U*Gold/Tin
S4: 15U*Gold/Tin
S5: 20U*Gold/Tin
S6: 30U*Gold/Tin
SN: Tin



Insulator
Material/Colour
B: PA9T/Black
C: PA6T/Black

Packing
T=Tube
P=Tube+Cap
R=Tape&Reel+Cap



Recommended P.C.B Layout(Top Side)

(PCB BOARD TOLERANCE±0.05)



Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: FHFM34-1XXXXXUX1

TITLE: FH2.54mm Single Row Female H=3.4mm SMT

NOTES:
Current Rating: 3.0AMP
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Withstand Voltage: 500V AC/Minute
Operation Temperature: -40°C to +105°C

MATERIAL:
Contact Material: Brass
Contact Plating: Au or Sn over Ni
Insulator Material: PA9T/PA6T+30%GF
(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X: ±0.40 ± 3°
X.XX: ±0.25
X.XXX: ±0.15

SCALE 1:1
UNIT MM
PROJ.
SHEET

A0	2015/06/25	NEW	Hua.ZT		Hua.ZT
REV	DATE	MODIFICATION DESCRIPTIO	DRAW	CHANGE	APPROVE