




Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE ± 0.05)





PART NUMBER CODING

FHER43- 1 XX XX X U X X

No.of Pins Row:02-40Pin	Contact Plating G0:Gold Flash G1:3U"Gold G2:5U"Gold G3:10U"Gold G4:15U"Gold G5:20U"Gold G6:30U"Gold S0:Gold Flash/Tin S1:3U"Gold/Tin S2:5U"Gold/Tin S3:10U"Gold/Tin S4:15U"Gold/Tin S5:20U"Gold/Tin S6:30U"Gold/Tin SN:Tin	Insulator Material/Colour A:PBT/Black B:PA9T/Black C:PA6T/Black	Packing A=Tray B=PE Bag T=Tube	DIM L 1=2.4 2=3.1
----------------------------	---	---	---	-------------------------

Dimensions Antitheses List

Part No.	DIM L
FHER43-1XXXXXUX1	2.40
FHER43-1XXXXXUX2	3.10



Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: FHER43-1XXXXXUX

TITLE: FH2.00mm Single Female H=4.3mm 90°

NOTES:
Current Rating:2.0AMP
Contact Resistance:20m Ω Max
Insulation Resistance:1000M Ω Min
Withstand Voltage:500V AC/Minute
Operation Temperature:-40°C to +105°C

MATERIAL:
Contact Material:Brass
Contact Plating:Au or Sn over Ni
Insulator Material:PBT/PA9T/PA6T+30%GF
(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X:±0.40 ± 3°
X.XX:±0.25
X.XXX:±0.15

SCALE	1:1
UNIT	MM
PROJ.	
SHEET	

A0	2015/06/25	NEW	Huan.Tan		Huan.Tan
REV	DATE	MODIFICATION DESCRIPTIO	DRAW	CHANGE	APPROVE