




Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE $\pm$ 0.05)



PART NUMBER CODING



FHEZ20-1 XX XX X U X 1

No. of Pins
Row: 02-40Pin

Contact Plating
G0: Gold Flash
G1: 3U" Gold
G2: 5U" Gold
G3: 10U" Gold
G4: 15U" Gold
G5: 20U" Gold
G6: 30U" Gold
S0: Gold Flash/Tin
S1: 3U" Gold/Tin
S2: 5U" Gold/Tin
S3: 10U" Gold/Tin
S4: 15U" Gold/Tin
S5: 20U" Gold/Tin
S6: 30U" Gold/Tin
SN: Tin

Insulator
Material/Colour
B: PA9T/Black
C: PA6T/Black

Packing
T=Tube
P=Tube+Cap
R=Tape&Reel+Cap



Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: FHEZ20-1XXXXXUX1

TITLE: FH2.00mm Single Female H=2.00mm 90° Side Enter Kink Feet

NOTES:
Current Rating: 2.0AMP
Contact Resistance: 20m Ω Max
Insulation Resistance: 1000M Ω Min
Withstand Voltage: 500V AC/Minute
Operation Temperature: -40°C to +105°C

MATERIAL:
Contact Material: Brass
Contact Plating: Au or Sn over Ni
Insulator Material: PA9T/PA6T+30%GF
(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X: $\pm$ 0.40 $\pm$ 3°
X.XX: $\pm$ 0.25
X.XXX: $\pm$ 0.15

SCALE 1:1
UNIT MM
PROJ.
SHEET

A0	2019/06/25	NEW	Jason.Huang		Jason.Huang
REV	DATE	MODIFICATION DESCRIPTIO	DRAW	CHANGE	APPROVE