




Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE ± 0.05)



PART NUMBER CODING


FHCS44-1 XX XX X U X 1

No. of Pins
Row: 02-50 Pin


Contact Plating
G0: Gold Flash
G1: 3U* Gold
G2: 5U* Gold
G3: 10U* Gold
G4: 15U* Gold
G5: 20U* Gold
G6: 30U* Gold
S0: Gold Flash/Tin
S1: 3U* Gold/Tin
S2: 5U* Gold/Tin
S3: 10U* Gold/Tin
S4: 15U* Gold/Tin
S5: 20U* Gold/Tin
S6: 30U* Gold/Tin
SN: Tin

Insulator
Material/Colour
A: PBT/Black
B: PA9T/Black
C: PA6T/Black


Packing
A=Tray
T=Tube



1.80 ± 0.15



4.30 ± 0.15



2.40 ± 0.25



Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: FHCS44-1XXXXXU1

TITLE: FH1.27mm Single Female 180° H=4.30mm

NOTES:
Current Rating: 1.0AMP
Contact Resistance: 20m Ω Max
Insulation Resistance: 1000M Ω Min
Withstand Voltage: 500V AC/Minute
Operation Temperature: -40°C to +105°C

MATERIAL:
Contact Material: Phosphor Bronze
Contact Plating: Au or Sn over Ni
Insulator Material: PBT/PA9T/PA6T+30%GF
(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X: ± 0.40 $\pm 3^\circ$
X.XX: ± 0.25
X.XXX: ± 0.15

SCALE 1:1

UNIT MM

PROJ.

SHEET

A0	2015/06/25	NEW	Huan.Tan		Huan.Tan
REV	DATE	MODIFICATION DESCRIPTION	DRAW	CHANGE	APPROVE