



PART NUMBER CODING

FHCM34- 1 XX XX X U X X


No. of Pins
Row: 02-40 Pin

Contact Plating
G0: Gold Flash
G1: 3U" Gold
G2: 5U" Gold
G3: 10U" Gold
G4: 15U" Gold
G5: 20U" Gold
G6: 30U" Gold
S0: Gold Flash/Tin
S1: 3U" Gold/Tin
S2: 5U" Gold/Tin
S3: 10U" Gold/Tin
S4: 15U" Gold/Tin
S5: 20U" Gold/Tin
S6: 30U" Gold/Tin
SN: Tin



Insulator Material/Colour
B: PA9T/Black
C: PA6T/Black

Packing
R=Reel+Cap
M=Reel+Mylar




Series No.
3=Type1
4=Type2



Type 2



Type 1



Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: FHCM34-1XXXXXUX

TITLE: FH1.27mm Single Female SMT H=3.40mm 塑宽=2.10mm

NOTES:
Current Rating: 1.0AMP
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Withstand Voltage: 500V AC/Minute
Operation Temperature: -40°C to +105°C

MATERIAL:
Contact Material: Phosphor Bronze
Contact Plating: Au or Sn over Ni
Insulator Material: PA9T/PA6T+30%GF
(UL94V-0)

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN METRIC TOLERANCES ARE:
DECIMALS Angle
X.X: ±0.40 ± 3°
X.XX: ±0.25
X.XXX: ±0.15

SCALE	1:1
UNIT	MM
PROJ.	
SHEET	

A0	2021/10/25	NEW	GF.He		Andy
REV	DATE	MODIFICATION DESCRIPTION	DRAW	CHANGE	APPROVE