



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE ± 0.05)

PART NUMBER CODING

PHJR25-11 XX XX X XXX X 1

No. of Pins
01-20

Contact Plating
G0:Gold Flash
G1:3U"Gold
G2:5U"Gold
G3:10U"Gold
G4:15U"Gold
G5:20U"Gold
G6:30U"Gold
S0:Gold Flash/Tin
S1:3U"Gold/Tin
S2:5U"Gold/Tin
S3:10U"Gold/Tin
S4:15U"Gold/Tin
S5:20U"Gold/Tin
S6:30U"Gold/Tin
SN:Tin




Insulator
Material/Colour
B:PA9T/Black
C:PA6T/Black
D:LCP/Black

Pin length
L=A+B+
D+5.56

Packing
B=PE Bag
T=Tube

Dinmension antitheses list

ITEM	A	B	D
Standard	3.50	6.00	0.00
Alternate			



Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: PHJR25-11XXXXXXXXX1

TITLE: PH 5.08mm Single ROW 90° H=2.5mm Plane Bending

NOTES:
Current Rating:7.0AMP
Withstand Voltage:500V AC/DC
Contact Resistance:20mΩ Max
Insulation Resistance:1000MΩ Min
Operation Temperature:-40°C to +105°C

Contact Material: Brass
Contact Plating:Au or Sn over Ni
Insulator Material:PA9T/PA6T/LCP+30%GF
(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X:±0.40 ± 3°
X.XX:±0.25
X.XXX:±0.15

SCALE 1:1

UNIT MM

PROJ.

SHEET

A0	2015/06/25	NEW	Huan.Tan		Huan.Tan
REV	DATE	MODIFICATION DESCRIPTION	DRAW	CHANGE	APPROVE