






Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05)





PART NUMBER CODING

PHFS25-22 XX XX X XXX X X



Dimension antitheses list			
ITEM	A	B	C
Standard	3.00	6.00	0.00
Alternate			



TYPE 1

TYPE 2



Tel: +86 769 82581808 FAX: +86 769 81766192
E-Mail: sales@winpin.net Http: www.winpin.net

PART NO: PHFS25-22XXXXXXXXXX

TITLE: PH 2.54mm Dual ROW 180° H=2.5mm Double Plastic

NOTES:
Current Rating:3.0AMP
Withstand Voltage:500V AC/DC
Contact Resistance:20mΩ Max
Insulation Resistance:1000MΩ Min
Operation Temperature:-40°C to +105°C

Contact Material: Brass
Contact Plating:Au or Sn over Ni
Insulator Material:PBT/PA9T/PA6T/+30%GF
(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X:±0.40 ± 3°
X.XX:±0.25
X.XXX:±0.15

SCALE	1:1
UNIT	MM
PROJ.	
SHEET	

A0	2015/06/25	NEW	Huan.Tan		Huan.Tan
REV	DATE	MODIFICATION DESCRIPTIO	DRAW	CHANGE	APPROVE