






Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE ± 0.05)



PART NUMBER CODING

PHDR25-22 XX XX X XXX X 1

No. of Pins 01-50	Contact Plating	Insulator Material/Colour	Pin length L=A+B+C +D+1.25	Packing B=PE bag T=Tube
G0:Gold Flash	A:PBT/Black			
G1:3U"Gold	B:PA9T/Black			
G2:5U"Gold	C:PA6T/Black			
G3:10U"Gold				
G4:15U"Gold				
G5:20U"Gold				
G6:30U"Gold				
S0:Gold Flash/Tin				
S1:3U"Gold/Tin				
S2:5U"Gold/Tin				
S3:10U"Gold/Tin				
S4:15U"Gold/Tin				
S5:20U"Gold/Tin				
S6:30U"Gold/Tin				
SN:Tin				



Dimension antitheses list

ITEM	A	B	C	D
Srandard	2.50	4.00		1.20
Alternate				



Tel: +86 769 82581808 FAX: +86 769 81766192
E-Mail: sales@winpin.net Http: www.winpin.net

PART NO: PHDR25-22XXXXXXXXXX1

TITLE: PH 1.27x2.54mm Dual ROW 90°H=2.5mm Double Plastic

NOTES:
Current Rating:1.0AMP
Withstand Voltage:500V AC/DC
Contact Resistance:20mΩ Max
Insulation Resistance:1000MΩ Min
Operation Temperature:-40°C to +105°C

Contact Material:Brass
Contact Plating:Au or Sn over Ni
Insulator Material:PBT/PA9T/PA6T+30%GF
(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X:±0.40 ± 3°
X.XX:±0.25
X.XXX:±0.15

SCALE	1:1
UNIT	MM
PROJ.	
SHEET	

A0	2015/06/25	NEW	Huan.Tan		Huan.Tan
REV	DATE	MODIFICATION DESCRIPTION	DRAW	CHANGE	APPROVE