

PART NUMBER CODING

PHBS10-11 XX XX X XXX X 1


No. of Pins
01-50

Contact Plating
G0: Gold Flash
G1: 3U" Gold
G2: 5U" Gold
G3: 10U" Gold
G4: 15U" Gold
G5: 20U" Gold
G6: 30U" Gold
S0: Gold Flash/Tin
S1: 3U" Gold/Tin
S2: 5U" Gold/Tin
S3: 10U" Gold/Tin
S4: 15U" Gold/Tin
S5: 20U" Gold/Tin
S6: 30U" Gold/Tin
SN: Tin



Insulator
Material/Colour
A: PBT/Black
B: PA9T/Black
C: PA6T/Black

Pin length
L=A+B+1.0



Packing
T=Tube
P=Tube+CAP
R=Tape&Reel+CAP



Dimension antitheses list		
ITEM	A	B
Standard	1.80	1.80
Alternate		



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Tel: +86 769 82581808 FAX: +86 769 81766192
E-Mail: sales@winpin.net Http: www.winpin.net

PART NO: PHBS10-11XXXXXXXXX1

TITLE: PH 1.0mm Single Row 180° H=1.00mm

NOTES:
Current Rating: 0.75AMP
Withstand Voltage: 500V AC/DC
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Operation Temperature: -40°C to +105°C

Contact Material: Brass
Contact Plating: Au or Sn over Ni
Insulator Material: PBT/PA9T/PA6T+30%GF
(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X: ±0.40 ± 3°
X.XX: ±0.25
X.XXX: ±0.15

SCALE	1:1
UNIT	MM
PROJ.	
SHEET	

A0	2015/06/25	NEW	Huan.Tan		Huan.Tan
REV	DATE	MODIFICATION DESCRIPTION	DRAW	CHANGE	APPROVE