




Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE ± 0.05)



PART NUMBER CODING



BHCS03- XX XX 1 X X 1

No. of Pins
06-100P

Contact Plating
G0:Gold Flash
G1:3U"Gold
G2:5U"Gold
G3:10U"Gold
G4:15U"Gold
G5:20U"Gold
G6:30U"Gold
S0:Gold Flash/Tin
S1:3U"Gold/Tin
S2:5U"Gold/Tin
S3:10U"Gold/Tin
S4:15U"Gold/Tin
S5:20U"Gold/Tin
S6:30U"Gold/Tin
SN:Tin

Material/Color
B:PA9T/Black
C:PA6T/Black
D:LCP/Black

Packing
A:Tray
T:Tube



Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: BHCS03-XXXX1XX1

TITLE: 1.27mm Box Header 180° H=4.9mm

NOTES:

Current Rating: 1AMP
Withstand Voltage: 500V AC/DC
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Operation Temperature: -40°C to +105°C

MATERIAL:

Contact Material: Brass
Contact Plating: Au or Sn over Ni
Insulator Material: LCP/PA9T/PA6T+30%GF
(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X: ± 0.40
X.XX: ± 0.25
X.XXX: ± 0.15

SCALE	1:1
UNIT	MM
PROJ.	
SHEET	

A0	2015/06/25	NEW	Hua.ZT		Hua.ZT
REV	DATE	MODIFICATION DESCRIPTIO	DRAW	CHANGE	APPROVE