




Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05)



PART NUMBER CODING



BHCR04 - XX XX 1 X X 1

No. of Pins
10-64P

Contact Plating
G0:Gold Flash
G1:3U"Gold
G2:5U"Gold
G3:10U"Gold
G4:15U"Gold
G5:20U"Gold
G6:30U"Gold
S0:Gold Flash/Tin
S1:3U"Gold/Tin
S2:5U"Gold/Tin
S3:10U"Gold/Tin
S4:15U"Gold/Tin
S5:20U"Gold/Tin
S6:30U"Gold/Tin
SN:Tin

Material/Color
B:PA9T/Black
C:PA6T/Black
D:LCP/Black

Packing
A:Tray
T:Tube



Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: BHCR04-XXXX1XX1

TITLE: 1.27mm Box Header 90° H=5.7

NOTES:

Current Rating: 1AMP
Withstand Voltage: 500V AC/DC
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Operation Temperature: -40°C to +105°C

MATERIAL:

Contact Material: Brass
Contact Plating: Au or Sn over Ni
Insulator Material: LCP/PA9T/PA6T + 30%GF
(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X: ±0.40 ± 3°
X.XX: ±0.25
X.XXX: ±0.15

SCALE 1:1

UNIT MM

PROJ.

SHEET

S						
	A0	2015/06/25	NEW	GF.He	_____	Andy
	REV	DATE	MODIFICATION DESCRIPTIO	DRAW	CHANGE	APPROVE