



PART NUMBER CODING

H25412-2 XX X 1

No.of pins
Per Row
02-32P

Color
B=Black

Pins	Dimensions		Pins	Dimensions	
	A	B		A	B
2*02	2.54	5.08	2*18	43.18	45.72
2*03	5.08	7.62	2*19	45.72	48.26
2*04	7.62	10.16	2*20	48.26	50.80
2*05	10.16	12.70	2*21	50.80	53.34
2*06	12.70	15.24	2*22	53.34	55.88
2*07	15.24	17.78	2*23	55.88	58.42
2*08	17.78	20.32	2*24	58.42	60.96
2*09	20.32	22.86	2*25	60.96	63.50
2*10	22.86	25.40	2*26	63.50	66.04
2*11	25.40	27.94	2*27	66.04	68.58
2*12	27.94	30.48	2*28	68.58	71.12
2*13	30.48	33.02	2*29	71.12	73.66
2*14	33.02	35.56	2*30	73.66	76.20
2*15	35.56	38.10	2*31	76.20	78.74
2*16	38.10	40.64	2*32	78.74	81.28
2*17	40.64	43.18			



Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: H25412-2XXX1

TITLE: 2.54mm Housing

NOTES:
Current Rating:3.0A AC/DC
Voltage Rating:250V AC/DC
Withstand Voltage:1500V AC/DC
Contact Resistance:20mΩ Max
Insulation Resistance:1000MΩ Min
Operation Temperature:-40°C~+105°C
Applicable Terminal:T25412-PXX1
Applicable Wafer:W25412-2XXXXXXX

MATERIAL:
Insulation :PBT (UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X:±0.40 ± 3°
X.XX:±0.25
X.XXX:±0.15

SCALE 1:1
UNIT MM
PROJ.
SHEET

A0	2015/06/25	NEW	Hua.ZT		Hua.ZT
REV	DATE	MODIFICATION DESCRIPTIO	DRAW	CHANGE	APPROVE

