



PART NUMBER CODING

W25001-1 XX R XX E X 3

No.of Pins
02-16P

Contact plating
SN: Tin

Color
E=Beige

Packing
B=PE Bag
R=Reel+Cap

Pins	Dimensions		
	A	B	C
02	2.50	6.10	7.50
03	5.00	8.60	10.00
04	7.50	11.10	12.50
05	10.00	13.60	15.00
06	12.50	16.10	17.50
07	15.00	18.60	20.00
08	17.50	21.10	22.50
09	20.00	23.60	25.00
10	22.50	26.10	27.50
11	25.00	28.60	30.00
12	27.50	31.10	32.50
13	30.00	33.60	35.00
14	32.50	36.10	37.50
15	35.00	38.60	40.00
16	37.50	41.10	42.50



Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: W25001-1XXRXXEX3

TITLE: 2.5mm Wafer 90°

NOTES:
Current Rating: 3A AC/DC
Voltage Rating: 250V AC/DC
Withstand Voltage: 1000V AC/Minute
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Operation Temperature: -40°C ~ +105°C

MATERIAL:
Contact: Brass
Contact Plating: Sn over Ni
Insulation: LCP, UL94V-0

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X: ±0.40 ± 3°
X.XX: ±0.25
X.XXX: ±0.15

SCALE	1:1
UNIT	MM
PROJ.	
SHEET	

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE ±0.05)

