



PART NUMBER CODING

H25413-2 XX X 1

No. of pins
02-32P

Color
B=Black

Pins	Dimensions		Pins	Dimensions	
	A	B		A	B
2*02	2.54	9.48	2*18	43.18	50.12
2*03	5.08	12.02	2*19	45.72	52.66
2*04	7.62	14.56	2*20	48.26	55.20
2*05	10.16	17.10	2*21	50.80	57.74
2*06	12.70	19.64	2*22	53.34	60.28
2*07	15.24	22.18	2*23	55.88	62.82
2*08	17.78	24.72	2*24	58.42	65.36
2*09	20.32	27.26	2*25	60.96	67.90
2*10	22.86	29.80	2*26	63.50	70.44
2*11	25.40	32.34	2*27	66.04	72.98
2*12	27.94	34.88	2*28	68.58	75.52
2*13	30.48	37.42	2*29	71.12	78.06
2*14	33.02	39.96	2*30	73.66	80.60
2*15	35.56	42.50	2*31	76.20	83.14
2*16	38.10	45.04	2*32	78.74	85.68
2*17	40.64	47.58			



Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: H25413-2XXX1

TITLE: HRS 2.54mm Housing

NOTES:
Current Rating: 3.0A AC/DC
Voltage Rating: 250V AC/DC
Withstand Voltage: 1500V AC/Minute
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Operation Temperature: -25°C ~ +85°C
Applicable Terminal: T25413-PXX1/2

MATERIAL:
Insulation: PBT, UL94V-0

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X: ±0.40 ± 3°
X.XX: ±0.25
X.XXX: ±0.15

SCALE	1:1
UNIT	MM
PROJ.	
SHEET	

